

Science Focus 7

UNIT D TEST Structures and Forces



This is a Crash Test Dummy.
Why was it designed to test vehicles impacts?



What kind of support structure is this?

(Hint: it was used on big cathedrals in Europe)



What kind of structure is this?

Student Name Class

1.		All of the following structures can be classified as manufactured, EXCEPT jigsaw puzzle
	В	a spoon
	С	a feather
	D	a fishing net
2.		The following are examples of natural mass structures
		dams and mountains brick walls and coral reefs
		ice sculptures and sand castles
		mountains and coral reefs
	_	mountains and cordineers
3.		How a structure is put together, how it is shaped and the types of materials that are used to build it are all part of the structure's
		design
		function
		classification
	D	stability
4.		'Running bond' is a pattern used for strength in dams
		brick walls
	С	beaver dams
	D	omelets
5.		Frame structures have a skeleton-like appearance and are made of very strong materials so they can support the
	Α	partition walls
	В	retaining walls
	С	load bearing walls
	D	roof and covering materials
6		Fig. cortains, food come, bettles and pines are examples of
6.		Egg cartons, food cans, bottles and pipes are examples of manufactured shell structures
		natural shell structures
		manufactured frame structures
		natural frame structures
	_	
7.		Containing, sheltering, transporting, lifting are all words to describe a structure's
	Α	design
	В	stability
	С	function
	D	aesthetics
8.		When a structure is built to withstand loads - more than it normally would carry - the structure is built with a larger foundation
	В	symmetrical base
	С	set of pilings
	D	margin of safety

A has a margin of safety B is esthetically pleasing C is cost effective D has a solid foundation 10. The following is an example of a composite material	
C is cost effective D has a solid foundation	
D has a solid foundation	
10. The following is an example of a composite material	
A a cardboard box	
B tent	
C drywall	
D reinforced concrete	
11. When choosing the most suitable materials to build a structure, architects, engineers and designers should all of the following before making their final choice	consider
A cost, appearance, environmental impact, energy efficiency	
B cost, color, life expectancy, impact strength	
C environmental appearance, type of symmetry, type of joints needed, cost effectiveness	
D flexibility, impact strength, energy efficiency, color	
12. Mobile joints are used to secure materials together in a structure. All of the following joints are examples of joints (allowing movement in a structure) EXCEPT	mobile
A a trailer hitch	
B photocopier lid	
C ball and socket joint (shoulder)	
D lego	
13. Adhesives are used to bind materials together. A type of adhesive that hardens when it cools isA thermosetting glue	
R therapoutic alue	
B therapeutic glue	
C solvent-based glue	
C solvent-based glue	
C solvent-based glue D solvent-enriched glue 14. The mass of an egg-sized lump of lead and the mass of an elephant	
C solvent-based glue D solvent-enriched glue 14. The mass of an egg-sized lump of lead and the mass of an elephant A are very different	
C solvent-based glue D solvent-enriched glue 14. The mass of an egg-sized lump of lead and the mass of an elephant A are very different B are about the same	
C solvent-based glue D solvent-enriched glue 14. The mass of an egg-sized lump of lead and the mass of an elephant A are very different	
C solvent-based glue D solvent-enriched glue 14. The mass of an egg-sized lump of lead and the mass of an elephant A are very different B are about the same C are measured in Newtons D would change if they were measured in different places	
C solvent-based glue D solvent-enriched glue 14. The mass of an egg-sized lump of lead and the mass of an elephant A are very different B are about the same C are measured in Newtons D would change if they were measured in different places 15. Weight is a force that is measured by the gravitational pull on the object. It is usually measured in	
C solvent-based glue D solvent-enriched glue 14. The mass of an egg-sized lump of lead and the mass of an elephant A are very different B are about the same C are measured in Newtons D would change if they were measured in different places 15. Weight is a force that is measured by the gravitational pull on the object. It is usually measured in A Newtons	
C solvent-based glue D solvent-enriched glue 14. The mass of an egg-sized lump of lead and the mass of an elephant A are very different B are about the same C are measured in Newtons D would change if they were measured in different places 15. Weight is a force that is measured by the gravitational pull on the object. It is usually measured in	

- 16. A student compared his mass in two different places (Vancouver and Banff). Which statement is correct?
 A His mass was unchanged.
 B His mass increased in Vancouver.
 C His mass decreased in Vancouver because it is at sea level.
 D His mass decreased in Banff because of the higher altitude.
- 17. 'Crush It' was an investigation activity that tested the strength of different types of shell structures. The manipulated variable in this activity was ...
 - A weight the shell could hold before it failed.
 - B mass the shell could hold before it failed.
 - C how long the shell performed its function.
 - D the different kinds of shell structures used.
- 18. Which force diagram show the forces happenning with a very active Weepic, while it is directly over the wall?



- **19.** The change in the shape or size of a structure can be due to internal forces which are produced by external forces acting on the structure and are called ...
 - A structural instability
 - B dead loads
 - C live loads
 - D deformation
- **20.** Bending or tearing a certain material, by pressing on different parts, in opposite directions, at the same time. The force you are creating is called ...
 - A shear force
 - B tension force
 - C torsion force
 - D compression force
- 21. A hurricane or tornado is an example of a force that can cause extreme damage to a structure when it acts on the structure, even for a short time. The environmental event is classified as a ...
 - A live load
 - B dead load
 - C deformation
 - D torsion event
- 22. Cross-country skis are designed to bend when a force is applied. Bending allows the middle of the ski to contact more snow, giving the skier a better grip when pushing off. The bending forces that are applied to the 'camber' (middle part of the ski) are ...
 - A compression and torsion
 - B tension and compression
 - C torsion and tension
 - D shear and torsion

23.	The strength of a certain material has been described by scientists as the forces between the tiniest particles of the material. Because the particles have yet to be seen, scientist can only make
Α	inferences
В	observation
С	analysis
D	conclusions
24.	Structures fail for a number of reasons. Engineers study failed structures so they can design stronger, more durable structures. A flagpole that has been blown over in a strong wind happens because of the increased force that is applied to the base of the structure making it act like a
Α	rib
В	lever
С	stringer
D	Inclined plane
25.	When a solid material is compressed, small microscopic cracks in the material can enlarge or break apart. This can cause one section of the material to break away from the other part. This action is called
Α	bend
В	buckle
С	shear
D	twist
26.	Crash test dummies are used by auto safety designers and inspectors to identify impact points when material fails in a collision. When the car is rammed into a solid wall, the front end buckles. This happens to better protect the Crash test dummies (us) in a real accident. The metal deforms because of the energy it absorbs in the impact. Designers
Α	identify where to reinforce the front end.
В	determine what materials buckle the least.
С	identify the weaknesses and try to fix them.
D	do this on purpose to increase the margin of safety.
27.	The designers of spinning wheels work to ensure that the fibers, that are twisted together, are done so tightly that they lock together. If the fibers are twisted too much they tangle and shorten, unless you keep pulling them apart. This can be useful if you are wanting to make
Α	lighter fabrics
В	stretchy fabrics
С	stronger fabrics
D	more durable fabrics
28.	Metal fatique happens because metal is

- A not made properly
- B too old to be used any more
- C exposed to extreme conditions
- D bent or twisted over and over again
- **29.** Designers generally use three key methods to help structures withstand forces. They include all of the methods below, **EXCEPT** for ...
 - A distribute the load evenly
 - B direct the forces along angled components
 - C place lighter materials above heavier materials
 - D shape the parts for the forces they are likely to face

D parallelograms A frame structure can support a very heavy roof because of one of the principles of design. The vertical 31. supporting posts in the structure visibly demonstrate this principle. The principle followed is ... A distribute the load evenly B direct the forces along angled components C shape the parts for the forces they are likely to face D place lighter materials above heavier materials 32. When a structure has a single horizontal load bearing beam, supported by two columns - one at each end, the beam will likely bend in the middle (A box and girder bridge spanning a 'raging river' is a good example). This bending exerts pressure outward on the vertical supporting beams. To strengthen this type of bridge, so that heavy vehicles can cross it, you should ... A reinforce the columns at both ends with braces B place additional columns in the middle C use a double cantilever design D utilize flying buttresses 33. Science fiction often gives us exciting ideas about materials that can withstand almost any force. In reality, the perfect material has not been discovered yet. One material (if it could be made the thickness of a pencil - could stop a 747 jet). It is currently being synthetically developed and will have widespread use because of its strength. The material is known as ... A Kelvar® B rice grain C spider silk D industrial bamboo Remember when you put your hands on your desk and put all your weight on them - then tried to move them forward? This demonstration was used to identify that your hand (much like a structure) resists movement forward because of ... A static forces **B** kinetic forces C external forces D frictional forces Stability in a structure is dependant on a number of factors. One of these factors is whether or not a structure could fail if an extreme force was applied to the structure that was not in the original design specifications. The World Trade Center Tower's collapse is example of a structure failing because it encountered a force beyond what it was designed to withstand. The Empire State building is a steel frame building that survived the crash of a USAF Bomber hitting it between the 78th and the 79th floors. The design component that likely enabled the Empire State building to withstand this incredible force was its ... A mass

Construction of a roof truss utilizes an important principle. Certain shapes will determine greater strength.

Because roofs need to be very strong, roof trusses are shaped in ...

30.

A rectanglesB squaresC triangles

B central locationC reinforced concrete

D lack of glass materials used

- **36.** The Leaning Tower of Pisa is an example of a mass structure. The Tower was built with a lean originally and it had been getting worse, because of the foundation on which it was built. The structure has not fallen over yet, because its center of gravity still keeps it relatively stable. Once it started to lean more, engineers knew that the center of gravity shifted. The reason that the Tower is moving is because ...
 - A it is very windy in Pisa
 - B Pisa has many earthquakes
 - C the thrust line is inside the foundation
 - D the thrust line is outside the foundation
- **37.** A firm foundation is necessary to support a structure. Solid ground is not always firm and stable. There are environmental and man-made conditions which make the soil loosen and become compact, which makes the soil relatively unstable. Three strategies are use to ensure a structure is built on a firm foundation. The three strategies include all of the following, **EXCEPT** ...
 - A spread the load
 - B make a soil layer
 - C find something solid
 - D utilize pressure and density
- **38.** Sometimes if a new invention comes along, it is based on a scientific principle. Again that is the case with the 'Segway. The one person motorized vehicle, that was recently unveiled, uses the principle *to gain stability of a forward moving object, you need to increase its speed*. This new invention utilizes this principle with one of its components, a ...
 - A gymnosperm
 - B gyroscope
 - C spinacre
 - D rotator disk
- **39.** The mass of a container of shampoo is 256 g. Its weight would be ...
 - A 0.256 kg
 - B 2.56 kg
 - C 0.256 N
 - D 2.56 N

40.



What kind of bridge is the illustration an example of?

- A trestle
- B box and girder
- C supported arch
- D double-cantilever